



TECHNICAL INFORMATION

ORIGEN OREX ULTRA 15W-40 HDDO Engine Oil

DESCRIPTION

ORIGEN OREX ULTRA 15W-40 CI-4 is a heavy-duty diesel engine oil. This engine oil is suitable to be used in a cross section of diesel engines that use a variety of different fuel qualities. It is suitable to be used in diesel engines that are fitted with exhaust gas re-circulation systems (EGR).

APPLICATION

ORIGEN OREX ULTRA 15W-40 CI-4 is suitable for use in high performance diesel engines where extended drain intervals are required.

API CI-4/SL	ACEA E7 7 A3/B4	DB 228.3/ 229.1
MAN M3275	VOLVO VOS-3	DEUTZ DQC III-10
ALLISON C4	DETROIT DDC 93K215	JASO DHD-1
CATECF2/1a	MTU DDC Type 2	MACK EO-N/EO-M PLUS
CUMMINS CES 20076/77/71/72/78.		

BENEFITS

- Superior levels of protection in high sulfur conditions.
- Improves engine efficiencies and fuel economy.
- Superior detergency and engine cleanliness.
- High resistance to bore polishing.

TECHNICAL CHARACTERISTICS

SAE	15W40
Density at 20°C kg.m-3	0.885
Viscosity at 40°C cSt	111
Viscosity at 100°C cSt	15
Viscosity Index	142
Flash Point	232
Pour Point	-40
TBN	10.5



1000lt



210lt



20lt



4x5lt



API
AMERICAN
PETROLEUM
INSTITUTE

*MSDS available on request.

Version 7: Mar 24

"Above and Beyond"