



6V/12V/24V

SMART BATTERY CHARGER



4A / 7.2A Battery Charger



Accessories:

Charger	AC Adapter(In)	DC Adapter(In)
4A	70.87	
8A		70.87



LCD DISPLAY

Shows working status




MULTIFUNCTION SWITCH

Power on/off or mode changing



11-SEGMENT INTELLIGENT CHARGING

Steady and safety



PLASTIC RUBBER CASE

Water-proof, solid and safe

MODEL	RC4000	RC7200
Rated Input Voltage AC	220-240 VAC	220-240 VAC
Working Voltage AC	170-260 VAC	170-260 VAC
Input Frequency	50-60Hz	50-60Hz
Input Current (at full charging current)	0.6A rms	1.1A rms
Efficiency	85% Approx.	85% Approx.
Charging Current	2A (12V & 6V), 4A (12V)	2A (12V & 6V), 8A (12V)
Low-Voltage Detection	2V (12V), 2V (6V)	2V (12V), 2V (6V)
Back Current Drain	1mA	1mA
Ambient temperature	-4°F to +122°F	-4°F to +122°F
Charger Type	11 Step, Smart Charger	11 Step, Smart Charger
Battery Chemistries	Wet, Gel, MF, CA, EFB, AGM	Wet, Gel, MF, CA, EFB, AGM
Battery Capacity	1.2-120Ah (12V), 1.2-60Ah (6V), Maintains All Battery Sizes	
Authentication	CE, GS, ROHS, IP65	CE, GS, ROHS, IP65
Product Dimension	10.6 x 5 x 3.3 in	13 x 5.8 x 3.7 in
Weight:	1.367 lb	2.26 lb

Smart Battery Charger

15A / 25A



15A / 25A Battery Charger



Accessories:

Charger	AC Adapter(In)	DC Adapter(In)
15A	70.87	
25A		70.87



LCD DISPLAY
Shows working status



MULTIFUNCTION SWITCH
Power on/off or mode changing



11-SEGMENT INTELLIGENT CHARGING
Steady and safety



PLASTIC RUBBER CASE
Water-proof, solid and safe

MODEL	RC15000	RC25000
Rated Input Voltage AC	220-240 VAC	220-240 VAC
Working Voltage AC	170-260 VAC	170-260 VAC
Input Frequency	50-60Hz	50-60Hz
Input Current (at full charging current)	2.1A rms	3.4A rms
Efficiency	85% Approx.	85% Approx.
Charging Current	2A, 10A, 15A (12V), 7.5A (24V)	2A, 15A, 25A (12V), 12.5A (24V)
Low-Voltage Detection	2V (12V), 2V (6V)	2V (12V), 2V (6V)
Back Current Drain	1mA	1mA
Ambient temperature	-4°F to +122°F	-4°F to +122°F
Charger Type	11 Step, Smart Charger	11 Step, Smart Charger
Battery Chemistries	Wet, Gel, MF, CA, EFB, AGM	Wet, Gel, MF, CA, EFB, AGM
Battery Capacity	1.2-400Ah (12V), 1.2-200Ah (24V), Maintains All Battery Sizes	
Authentication	CE, GS, ROHS, IP65	CE, GS, ROHS, IP65
Product Dimension	8.66 × 5.59 × 5.31 in	10.1 × 8.3 × 5.6 in
Weight:	2.7 lb	3.9 lb