



TECHNICAL INFORMATION

ORIGEN VISCO SYN 5W-30 C3 Synthetic Engine Oil

DESCRIPTION

ORIGEN VISCO SYN 5W-30 is a **mid SAPS** synthetic motor oil compatible with low emission catalytic converters fitted to modern passenger cars. Formulated with high performance synthetic base oils and fortified with advanced additive technology to boost performance and provide protection in extreme conditions. Advances in engine technology have led to increased power and efficiency outputs resulting in engines having to work harder than before. Our synthetic base oil technology provides excellent film strength in severe operating conditions which allows this engine oil to meet international OEM standards.

APPLICATION

ORIGEN VISCO SYN 5W-30 is suitable for use in high performance, high revving, multi valve, turbocharged and supercharged engines requiring an **API SN, ACEA C3**, Meets VW 502.00/505.00, MB 229.3, Renault 710/700.

BENEFITS

- Superior levels of protection in severe conditions.
- Improves engine efficiencies and fuel economy.
- Superior detergency and engine cleanliness.
- Superior wear protection and oxidation stability.

TECHNICAL CHARACTERISTICS

SAE	5W-30
Density at 20°C kg.m-3	0.860
Viscosity at 40°C cSt	73
Viscosity at 100°C cSt	11.7
Viscosity Index	171
Flash Point, °C	>200
Pour Point, °C	-42
Sulphated Ash, %wt	0.8



210lt



20lt



4*5lt

*MSDS available on request.

Version 4: Aug 25

