

Mobile unit with solar charge controller

Lithium

Features:

- Pure sine wave output
- 2000 cycles lifePO4 battery
- Mains supply mode, Battery mode
- 5VDC USB 2.0 ports
- 12VDC output ports
- MPPT solar charge controller
- Over charge protection as well as over discharge protection
- Intelligent exhaust fan



Inverter Specs	
Rated Power	2 000VA / 2 000W
Input	
Voltage range	170 - 275V
Mains charging current	10A
Frequency Range	45-65Hz
Output	
Voltage	230V AC
Frequency	50/60Hz
Output wave form	Pure Sine Wave
Battery	
Battery Voltage	25.6V DC
Battery capacity	1X 100Ah
Battery cycle life	2 000 Cycles @ DOD 80%
Solar Charger	
Solar Charge Type	MPPT
Maximum PV Array Power	820W
Number of MPPTs	1
MPPT Range @ Operating Voltage	35 - 100V DC
Maximum Solar Charge Current	30A
Floating charge voltage	28.4V DC
DC Output	
Low Voltage Recovery	26.8V DC
Low voltage protection	22.4V DC
5V DC USB Output	2 Pcs 5V DC, USB 2.0, Max 2A
12V DC Output Ports	2 Pcs Max 2A
Physical	
Heat Dissipation / Cooling	Intelligent exhaust fan (Temperature controlled)
Dimensions W X D X H (mm)	497 X 282 X 440
Package size W X D X H (mm)	557 X 377 X 515
Net Weight (kgs)	45kg
Gross Weight (kgs)	48kg

Product specifications are subject to change without further notice.

