



TECHNICAL INFORMATION

ORIGEN SYNTELO 5W-30 SP Fully Synthetic Engine Oil

DESCRIPTION

ORIGEN SYNTELO 5W-30 SP is a synthetic motor oil formulated with high performance base oils and highly advanced additive technology developed for naturally aspirated and turbocharged petrol and diesel passenger cars and LCVs. Advances in engine technology have led to increased power density resulting in higher combustion temperatures.

ORIGEN SYNTELO 5W-30 SP synthetic base oils resist oxidation, providing excellent lubricity under severe operating conditions. Note: Syntelo 5W-30 is not suitable for vehicles fitted with after-treatment devices, requiring low ash (SAPS) products.

APPLICATION

ORIGEN SYNTELO 5W-30 SP is suitable for use in high performance, high revving, multi-valve, turbocharged and supercharged engines meeting the following specifications: API SP/SN/CF, ACEA A3/B4-21, VW 502.00/505.00, MB 229.5, Renault 710/700. Suitable for vehicles prone to Low-Speed Pre-ignition (LSPI).

BENEFITS

- Superior levels of protection in arduous conditions.
- Improves engine efficiencies and fuel economy.
- Superior detergency and engine cleanliness.
- Superior wear protection and oxidation stability.
- Meets API SP: Low Speed Pre-Ignition (LSPI) compatible.

TECHNICAL CHARACTERISTICS

SAE	5W30
Density at 20°C kg.m-3	0.842
Viscosity at 40°C cSt	80
Viscosity at 100°C cSt	12.5
Viscosity Index	170
Flash Point	190
Pour Point	-40



210lt



20lt

*MSDS available on request.

Version 1: Aug 25

