



TECHNICAL INFORMATION

ORIGEN R Full Synthetic 5W-40 Racing Oil

DESCRIPTION

ORIGEN R 5W-40 is full synthetic PAO based, passenger car motor oil, fortified with advanced additive technology and high quality hydrocracked base stocks to boost performance and provide protection in extreme conditions. Advances in engine technology have led to increased power-density ratio and efficiency resulting in increased load and higher operating temperatures. Formulated with full synthetic base oil technology provides excellent film strength and oxidation stability in severe operating conditions. The product meets the stringent requirements of most OEM specifications. **Origen R 5W-40** is specifically designed for competition and endurance conditions and applications that have high revving engines with higher than normal operating temperatures.

APPLICATION

ORIGEN R 5W-40 is suitable for use in high performance, high revving, multi valve, turbocharged and supercharged engines requiring an **API SN/CF, ACEA A3/B4, VW 502.00/505.00, MB 229.5, Porsche A40, Renault 710/700, PSA Level 3 (B71 2296), BMW LL-01.**

BENEFITS

- Exceptional thermal stability and endurance.
- Improved engine protection at low temperature.
- Less drag and increased power output under racing conditions
- High oxidation stability.

TECHNICAL CHARACTERISTICS

SAE	5W40
Density at 20°C kg.m-3	0.860
Viscosity at 40°C cSt	77
Viscosity at 100°C cSt	13
Viscosity Index	171
Flash Point	250
Pour Point	-52



4x5lt



12x1lt

*MSDS available on request.

Version 8: Aug 25

