



TECHNICAL INFORMATION

ORIGEN CAL-S-TAC 2

Synthetic Calcium Sulphonate EP2 Grease

DESCRIPTION

ORIGEN CAL-S-TAC 2 is a blend of calcium sulphonate NLGI 2 grease, fortified with synthetic polymers. **ORIGEN CAL-S-TAC 2** is an excellent lubricant for high temperature and wet industrial and automotive applications. This grease provides outstanding mechanical and thermal stability, has very high load carrying characteristics and provides good resistance to corrosion in the presence of water.

APPLICATION

ORIGEN CAL-S-TAC 2 is recommended for large plain and anti-friction bearings as well as mechanisms which require high temperature grease such as slides and cams. It has good adhesive qualities, good pumpability and reduces re-lubrication intervals.

BENEFITS

- Operating temperatures from -15°C to +180°C.
- Extends lube cycles, high resistance to water wash-out and spray off.
- Outstanding corrosion and rust protection.
- Excellent load carrying ability.
- Acts as a sealant against dust.

TECHNICAL CHARACTERISTICS

NLGI	2
Thickener type	Calcium Sulphonate
Worked penetration @ 25°C	265 – 295
Drop Point °C	>280
Oil viscosity cSt @ 40°C	200
Corrosion Test	Pass
Rust Test	Pass
Water Washout Test	Pass
Colour	Beige, Brown



50kg



15kg



*MSDS available on request.

Version 3: Aug 25